

COST OF ELECTRICITY LOAD SHEDDING TO MINES IN ZIMBABWE: DIRECT ASSESSMENT APPROACH

***Kaseke, N.**

Hosking, S. G.

*Department of Economics and Economic History
Nelson Mandela Metropolitan University
Port Elizabeth, 6031, Eastern Cape, South Africa*

**E-mail: nykaseke@gmail.com*

ABSTRACT

Zimbabwe's mining sector has been hit hard by electricity load shedding from the power utility. Load shedding was seen as a solution to the inability of power utility to supply electricity to meet demand. Electricity supply problems has so many cause and some of which are inability to expand generation capacity, aging equipment, droughts, cost coal supply to thermal plants, vandalism and political disturbances. Mines flooded as a result of poor pumping of water outside the tunnels and mine shafts, and also lost productive hours of production. This study applied the direct assessment approach to estimate the cost of load shedding. A survey method was adopted for the mines as they are scattered. A questionnaire was opted as a research instrument and was administered to mine captains. The results revealed that low capacity mines incurred higher load shedding cost compared to high capacity mines. It was also observed that high valued mineral mines (gold, diamond and platinum mines) incurred high outage cost as compared to low valued mineral mines (vermiculite, graphite and phosphate). From the study it can be concluded that electricity load shedding resulted in high cost to mining sector in Zimbabwe. It is recommended that the power utility should increase power supply to minimise the load shedding and cost of load shedding.

Keywords: *Load, shedding, electricity, mining, cost, direct assessment.*

INTRODUCTION

Zimbabwe's Mining sector has been recovering from the plunging time of hyperinflation and low world prices. Zimbabwe has not been able to solve the electricity crisis problem. Zimbabwe is endowed with mineral wealth, which has been unsuccessfully exploited for economic development of the country (Confederation of Zimbabwe Industries (CZI) 2009). The range of minerals includes gold, coal, nickel, platinum, diamond, chrome and cobalt. Gold, diamonds and platinum are notably Zimbabwe's foreign currency cash cows. However, the exploitation of these minerals has been hampered by persistent electricity load shedding. Mining takes the third position in terms of GDP contribution at about 12.7% and is the second foreign currency earner (ZIMSTATS 2009).

This significant contribution to GDP and economic activities explains why mining is a highly regulated sector. The growth in the mining sector has been driven by the key sub-sectors, including platinum group metals (24%), gold (77%), chrome (147%) and coal (40%) from the previous year - 2008 (Chamber of Mines of Zimbabwe 2010). The diamond sector is expected to become a significant contributor going forward if the disputes

with KPCS are sorted out (Chamber of Mines of Zimbabwe 2010). The key legislation governing this sector is the Mines and Minerals Act (Chapter 21:05), the Minerals Marketing Corporation of Zimbabwe Act (Chapter 21:04) and the Chamber of Mines of Zimbabwe. The said legislation provide for the licensing, exploration and marketing of minerals in Zimbabwe. Zimbabwean government acknowledges the importance of the mining sector to the socio-economic development of the country. Currently, the sector employs an average of 55000 people formally per annum (ZIMSTATS 2009; CZI 2009 and Chamber of Mines of Zimbabwe, 2010).

The figure has been higher than this before but due to downturn of global market prices, world recession and other problems domestically such as political environment and power outages; the sector is not spared but to cut employment (CZI 2009). Many mine sites are remotely located with respect to grid feeder lines (Ministry of Mines 2009). Therefore, they have their direct connection using own transformers (ZESA, 2009). This makes it easier to treat mines independently. Consequently, this study sought to estimate cost of load shedding to the mining sector in Zimbabwe. Electricity is demanded greatly for mining operations. Continuous load shedding make lives of mining labourers to be on danger. The researchers proposed a survey framework to elicit cost of outages.

THE ZIMBABWEAN PROBLEM

Power shortages in Zimbabwe are not a problem for mines only but for the whole nation. The unprecedented meltdown of Zimbabwe's economy can easily be traced to self-engineered political instability by the government. Subsequently, the roots of political instability further led to economic mismanagement and corruption in the economy. When in November 1997 it was announced that war veterans were to be given non-budgeted payments of magnitude which threatened fiscal targets, external investors bolted out of the Zimbabwe Stock Exchange, and domestic market foresaw an imminent devaluation, the Zimbabwe dollar crashed by almost a fourth of its value in local currency terms and it has been sliding by the day since that time. This proved to be the start of real crisis of management of the economy. By the end of 1999 the Zimbabwe economy was already in a severe macroeconomic crisis: GDP had fallen to below two percent, inflation had average 58.5 percent and exports had stagnated, forcing sharp contraction of imports (ZESA, 2001). The government pursued a political agenda instead of formulating an agenda to tackle this downward tumble which further impacted negatively on the economy. From February 2000 the government of Zimbabwe voluntarily abrogated the rule of law by allowing farm invasions, political harassment and murders. The underlying causes of Zimbabwe's economic crisis had started, with its political roots embedded in two main factors:

- Economic activity disruptions as a result of state-sponsored lawlessness; and
- Brushing aside decisions of the law courts by the sitting government.

This clearly undermined business confidence, affected current output and decimated investment, causing fuel shortages, accumulation of arrears in international payments and an increase in the budget deficit. The government has refused to acknowledge the importance of the environment under which economic progress takes place, and that any improvement

of macroeconomic management, investments, liberalization of markets and trade and widening of the space for the private sector activity have to be invariably underpinned by good governance and civic peace. Thus from 1997 the one party government adopted a total irresponsible politically driven economic management system that finally culminated in the 2000 illegal farm invasions and violent disruptions of economic activities that have proved that such venality leads to unsustainable and irretrievable economic downfall of the economy. Zimbabwe is now being ostracized by her major traditional trading partners.

While there are no explicit measures that are being imposed by regional partners the Southern Africa Development Community (SADC), The common Market for East and Southern Africa (COMESA) and the African Union (AU) Zimbabwe has been effectively isolated from many international regional pacts currently enjoyed by other countries in the region. Poor governance and political instability affected domestic electricity production and electricity import facilities. Zimbabwe was cut from the Southern African Power Pool (SAPP) grid due to non-payment and problems within other members of the group. ZESA Holdings is the nucleus of the generation, transmission and distribution of electricity in Zimbabwe. Zimbabwe has five major power stations, with a total capacity of 1240 MW (ZESA, 2007). These facilities do not meet electricity demand. Electricity generation in Zimbabwe is mainly from coal and hydro plants, with a capacity of 1240 MW, while the Kariba hydropower plant generates 780 MW as shown in table 1 (ZESA 2009).

Table 1: Power Station in Zimbabwe

Station	Plant type	Capacity (MW)	AC (MW)
Kariba	Hydro	780	740
Hwange	Coal	460	460
Harare	Coal	0	0
Bulawayo	Coal	0	0
Munyati	Coal	0	0
Total		1240	1240

Source: ZESA (2009). AC = Available capacity

In a bid to solve the problem of power shortages, the country resorted to importation. Zimbabwe used to import 35% of its electricity from neighbouring countries, including the DRC, Mozambique and Zambia (ZESA, 2009).

Table 2: Zimbabwe Power Imports

Country	IV(kv)	MC(mw)	AC(mw)
Mozambique		300	300
South Africa		0	0
Zambia	100	50	50
DR Congo		100	100
Botswana		0	0

Source: ZESA (2009). IV = Interconnection Voltage; MC = Maximum capacity; AC = Available capacity

From table 2 it can be seen that the country is not importing much resulting in wider gap between demand and supply. Under capacitated domestic production and lack of imports had created shortages which result in power outages through planned or unplanned load shedding.

Load Shedding started as early as 1997 (Kayo, 2001). Generation plant availability started to decline. Total systems losses have averaged 11% in 1997 (ZESA, 2007). The Zimbabwean dollar started depreciating against major currencies. Since over 70% of ZESA are imports of foreign currency related, proper plant, transmission and distribution equipment maintenance was impossible (ZESA, 2006). Consequently, ZESA was exposed to foreign exchange fluctuations and also was ill-equipped to manage this risk because of government controls on pricing and the end result was that the tariff had been eroded by the fluctuations (Kayo, 2001). ZESA relied much on government support financially to manage the situation at the least minimum load shedding to the consumers. ZESA's costs of operations have increased considerably, particularly those related to payment for import of power in foreign currency and servicing of foreign debt (ZESA, 2006).

Serious electricity load shedding started in 2000 soon after the land reform program in Zimbabwe (Kayo, 2001). The country was starved of foreign currency required to meet importation of fuel and electricity (Ministry of Energy and Power Development, 2005). Foreign suppliers demanded advance payment before electricity is supplied. Foreign currency crisis incapacitated importation of spare parts for plant maintenance. Cost of transporting coal from Hwange (coal mine) to Bulawayo, Munyati and Harare Thermal Power Stations (TPSs) and high maintenance cost to these TPSs resulted in decommissioning of the three TPSs. The TPSs used to contribute (Bulawayo 370MW, Harare 200MW and Munyati 100MW) to the grid (ZESA, 2006).

Decommissioning of TPSs worsened the supply of electricity in 2005 when total generation falls below 50% due to 2005/2006 drought (Ministry of Energy and Power Development, 2005). The supply was constrained whereas demand was growing high from growth in urban households, rural and growth point electrification (ZESA, 2007). In 2006, Zimbabwe was blackmailed for political reasons, suffered foreign currency deficits, tight economic sanctions, hyper-inflation, coal mine squabbles and high brain drain which further worsens power generation problems (ZESA, 2006).

Even though Zimbabwe is well networked in the Southern Africa, pressure amounted to foreign suppliers specifically South Africa due to its high domestic demand, Zimbabwe was disconnected from ESKOM supplies in 2007 (ZESA, 2007). The problem is threatening the whole region; Zambia is also experiencing the power cuts. Imports from Zambia, Democratic Republic of Congo (DRC) and Mozambique were cut due to payment problems. ESKOM has converted the debt of electricity to a loan in order to cover its expenses (ZESA, 2007). Zimbabwe has to depend solely from its on domestic generation and the guaranteed 100MW from Mozambique. Zimbabwe faced transmission, distribution and supply infrastructural problems and the West in 2007 due to vandalism. The Electricity Amendment Bill (Number 17) of 2007 stated that vandalism is becoming worse and stiffer penalties need to be implemented to those caught on the wrong side of the law. ZESA technicians and engineers also blamed the poor quality transformers and related equipment being acquired (ZESA, 2009). The performance of these equipment resulted in high levels of network electricity losses of 17% in 2009. Maintenance was and is still a big issue in ZESA, qualified engineers, artisans and technicians are leaving for neighbouring countries,

with the highest loss in 2007 of eighty engineers and artisans (ZESA, 2008). The generation of electricity in 2009 was at 55% of the potential capacity (ZPC, 2009). To meet local demand the rest had to be imported (ZESA, 2009). Total electricity supply fell well below demand. To manage the load, the power utility provider resorted to planned and unplanned load shedding. The supply of electricity in Zimbabwe depends on weather conditions because the latter affects water levels for electricity generation at the Kariba Hydro Power Station (HPS) and reliability of coal supply to Hwange thermal power station (TPS). The latter consumes about 6,000 to 9,000 tonnes of coal per day (ZESA, 2009). Due to predictability of peak demand per day and shortages of electricity supply to meet demand, ZESA drafted a load shedding programme for its customer sectors showing the times they would be cut off from power supply (table 3). The load shedding time table shows the times that consumers would be shed off from the national grid supply.

Table 3: Load shedding program for 2009 and beyond

Customer category	PERIOD			
	Morning (0400-1030 hrs)	Noon (1030-1700hrs)	Evening (1700-2100hrs)	Night (2100-0400hrs)
Industrial and mining (24 hour)	ON (reduced demand by 50%)	ON	ON (reduced demand by 50%)	ON
Industrial-12 hour	OFF	ON	OFF	OFF
Commercial (CBD)	OFF	ON	OFF	ON
Agricultural	OFF	ON/OFF	OFF	ON
Domestic: Urban	ON	ON/OFF	ON	ON
Domestic: Rural	OFF	ON/OFF	OFF	ON

Source: ZESA (2009). *M = Morning; Nn = Noon; E = Evening; N = Night*

Notes: (1) Load shedding applies to all areas in the country, (2) The programme applies for all days of the week, (3) Essential services (water works, sewers, hospitals and CBD of Harare and Bulawayo) will not be load shed; (4) Business customers on residential feeders follow domestic timetable, (5) Growth points and small towns follow rural timetable, and (6) Industrial customers to be switched off if they do not reduce demand during off peak.

LOAD SHEDDING OR ELECTRICITY OUTAGE

The electricity outages (load shedding) have attracted interest from various scholars over the last three decades (Ukpong, 1973; Ontario Hydro, 1980; Bernstein and Heganazy, 1988; Lee and Anas, 1992; Tierney 1997; Beenstock, Goldin and Haitovsky, 1998; Primen, 2001; Rose and Lim, 2002; Eto, Divan and Brumsickle, 2004; Eto et al. 2001; Rose, Oladosu and Salvino, 2004; Adenikinju, 2005; Bose, Shukla, Srivastava and Yaron, 2006). The general conclusion has been that power outages cause significant direct and indirect costs. Empirical evidence links the scale of these costs to variables such as electricity consumption per capita and the number of hours with/without electricity per day. Load shedding is an organised form of electricity outages (Eto, Divan and Brumsickle 2004).

Energy supply reliability improved after the 1950s coincided with rising global economic growth (World Bank, 2004). Energy is a prerequisite for economic growth and development (Ebohon, 1996; Rosenberg, 1998; Templet, 1999; Boston Institute for Development Economics, 2006; Foster and Steinbuks, 2008; Calderon, 2008). Energy has been shown to be equally as important in production as other factors such as labour, land and capital (European Commission, 1993). The relationship between economic growth

and electrical power demand has been found to be close (European Commission, 1993; Rosenberg 1998; Andrews-Speed and Dow, 2000; Ferguson, Wilkinson and Hill, 2000). Energy consumption is positively correlated to economic growth (Akinlo, 2008).

A study by Ferguson, Wilkinson and Hill (2000) that compared correlations between electricity consumption/capita with those between total primary energy supply/capita and GDP per capita showed that there is a stronger correlation between electricity use and wealth creation than there is between total energy use and wealth. Ferguson, Wilkinson and Hill (2000) also show that in wealthy countries an increase in wealth over time correlates with an increasing proportion of energy used in the form of electricity. In eleven Sub-Saharan African countries energy consumption is positively correlated to economic growth (Akinlo, 2008). Lee and Chang (2006) studied on the impact of energy consumption on economic growth in Taiwan, using data for the period 1955-2003, found evidence of a level-dependent effect between the two variables, energy consumption and economic growth. A study on the challenges of emerging Asia attributed the accommodation of increased energy consumption as a key contributor to 'miracle growth' (Asian Development Bank (ADB) 1997). Increased energy consumption is correlated with increased life expectancy, improved health, decreased mortality rates and improved productivity since the 1940s.

A World Bank study (1998) found that improved energy supply contributed approximately 0.8 to 1.9 percent of the accelerated annual growth of the Asian Tigers. Increasing electricity use has also been a foundation for all productivity improvements in developed countries and it now fuels the new digital economy (Pineau, 2002). Electricity facilitates an array of end-use equipment, including those for cooking, cooling, lighting, safe storage of food, clean water and sanitation (Ikeme and Ebohon, 2005).

METHODOLOGY

The methodology of the direct assessment approach uses direct loss by which it estimates the cost of power outages through lost production, lost materials and lost time. The direct assessment method is an economic appraisal tool that estimates the cost of power outages by allowing electricity consumers to express their losses in monetary terms (Bose et al. 2006). The approach is based on the principle that the lost production, materials and time in each productive sector, or lost goods during an outage (load shedding), can be estimated directly, and this can be aggregated to a total (De Nooij, Kopmans and Bijvoet, 2006). The approach relies on the individual respondent's self assessment method of valuing the cost of electricity outage. Direct cost estimations, such as the direct financial evaluation approach, the gross economic indices approach (GNP divided by total electricity consumption), and the case study approach have been frequently employed in the past (Pollitt, Jamasb and Yu, 2006).

In order to estimate the cost of load shedding by the direct assessment, it is important that total value lost by consumers due to load shedding is ascertained by summing all direct cost experienced during load shedding. The direct costs incurred by firms go beyond production loss or output loss. In addition to output loss cost, other direct costs such as

materials destruction cost (in stock), labour cost (payment of idle labourers and cost of overtime and bonuses to meet production and orders), damage to equipment cost, restart cost, time or opportunity cost per load shedding are part of the load shedding cost.

$$TDC_i = OL_i + MC_i + LC_i + EDC_i + RC_i \text{ ----- 1}$$

Where: TDC_i is the total direct cost for the i th consumer; OL_i is cost of lost output (lost leisure for households); MC_i is the material destruction cost; LC_i is labour cost; EDC_i is the equipment damage and maintenance cost as a result of load shedding; and RC_i is restart cost.

From equation 1 cost per unit of electricity (kwh) lost can be estimated as:

$$OC_i = \frac{TDC_i}{kWh_{los_i}} \text{ ----- 2}$$

Where: OC_i is the cost per kwh lost and kWh_{los_j} are the total units of electricity (kwh) lost or unsupplied due to load shedding.

METHODOLOGY

The questionnaire used in the mining sector load shedding cost survey was designed in consultation with focus groups, that is, Ministry of Mines, Minerals Marketing Corporations of Zimbabwe (MMCZ), ZESA, Ministry of Energy and Power Development and Mining captains. It was deemed important to understand the electricity load shedding impacts on mines, how they experienced the load shedding, the frequency of the load shedding, the time of the load shedding, the length of load shedding, losses they incur as a result of load shedding and alternative sources available common to mines.

The final questionnaire consisted of two parts. The first part contained questions about the mine considerations, that is, mineral extracted, location, hours of operation, hours of load shedding and the frequency of load shedding, uninterrupted power supply and advance warning arrangement, ranking of electricity infrastructure and other publicly provided infrastructural facilities. The second part included the direct cost estimation of load shedding. This part solicited actual load shedding cost: level of operation affected by load shedding, monthly production losses, damage to equipment, labour cost of idle staff, labourers employed and those laid off and deterred investment as a result of power load shedding. Before the questionnaire was validated, it was tested in smaller focus groups followed by a final survey study of administering of 120 copies of questionnaire to 120 respondents. The survey population includes all mines connected to the utility grid. The total population for mine consumers is shown on Table 4.

Table 4: ZESA mining electricity supply capacity classification

Tariff Class	Total Number of Customers
Low Capacity (LC) Mining	123
High Capacity (HC) Mining	48
Total	171

Source: ZESA (ZEDTCO), (2009)

Multistage sampling design was adopted for the mining electricity load shedding cost estimation survey. Mines were first stratified into low capacity (LC) and high capacity (HC) mines as per utility electricity supply capacity classification as shown on table 4. The second stratification was in terms of the mineral exploited. 14 minerals highly mined in Zimbabwe were considered. These minerals include gold, platinum, limestone, iron, vermiculite, phosphate, chrome, nickel, diamond, coal, lithium, graphite, black granite and asbestos. The selection of the type and units for the survey was based on secondary data on electricity purchased, sanctioned load, electricity generated by captive units and also utility recommendations. The sample size was reached by applying the Cochran (1977) approach to sample determination. This approach makes an assumption that there is normal distribution of the estimated sample size. The sample size estimates for the selected mine electricity consumers are shown on table 5.

Table 5: Sample sizes based on electricity tariff classification

Tariff Class	No. of Customers	Sample Size	%SS
Low Capacity Mining	123	85	69
High Capacity Mining	48	35	73
Total	171	120	70

Table 5 shows close link between electricity consumption through tariff classification from the utility (ZESA) and the number in the sample. This suggests that the sample may be considered an acceptable representation of the population. The actual mining survey was administered by the researchers and research assistants, who were trained on administering the questionnaires. Personally administered questionnaire survey was used to collect the data in order to reduce misinformation biases. The respondents were informed of the purpose of the research in advance through telephone or electronic mail (e-mail). The data from the questionnaires were cleaned, coded, collated as Excel spreadsheets and Statistical Package for Social Scientists (SPSS) 13 and E-views 6 were used for data analysis.

RESULTS AND DISCUSSION

A total of 74 out of the 120 questionnaires were successfully collected and analysed. The distributions of the mines by electricity supply capacity, scale of operation, location and mineral mined are shown on table 6. For the purpose of this survey, mines connected to voltage supply of below 300KVA were regarded as Low Capacity (LC) and those above 300KVA as High Capacity (HC). Mines employing less than 150 were classified as small scale, between 150 and 450 medium scale and above 450 large scale. Table 6 shows that 41.9% are HC mines and 58.1% are LC mines. About 40.5% are small scale mines, 27.1% medium scale and 32.4% large scale.

The survey reported that most mines are located in other areas and others around cities or towns. The mines selected spread across mineral type extracted, gold being the highly mined mineral and vermiculite and graphite are the lowest.

Table 6: Respondents distribution by power supply capacity, mineral, scale and location

Item of Analysis	Consideration	Frequency	Percentage
Power Supply Capacity	High Capacity (HC) mines	31	41.9
	Low Capacity (LC) mines	43	58.1
Scale of Operation	Small Scale (SS)	30	40.5
	Medium Scale (MS)	20	27.1
	Large Scale (LS)	24	32.4
Location	Harare	7	9.5
	Bulawayo	1	1.4
	Mutare	2	2.7
	Kwekwe	10	13.5
	Kadoma	7	9.5
	Chegutu	3	4.1
	Chinhoyi	3	4.1
	Other areas	41	55.4
Mineral Mined	Gold	32	43.2
	Platinum	5	6.8
	Limestone	5	6.8
	Iron	5	6.8
	Vermiculite	1	1.4
	Phosphate	3	4.1
	Chrome	9	12.2
	Nickel	1	1.4
	Diamond	3	4.1
	Coal	2	2.7
	Lithium	2	2.7
	Graphite	1	1.4
	Black Granite	3	4.1
Asbestos	2	2.7	

The crisis of electricity supply to the mining sector and economy can be seen on Table 7, 8, 9 and 10 which confirm the load shedding problem. On average, mines experienced load shedding 5 times a week and the load shedding times ranged from a minimum of 1 to a maximum of 7 per week (Table 7). About 41.9% mines surveyed experienced 5 load shedding per week, 8.1% mines experienced load shedding daily and also 8.1% mines experienced a single load shedding per week. No mine has reported zero load shedding per week reflecting that all mines were exposed to the power problem although frequencies differ.

Table 7: Frequency of weekly load shedding experienced by mines

<i>Load shedding per week</i>	Frequency	Percentage
1	6	8.1
2	2	2.7
3	11	14.9
4	9	12.2
5	31	41.9
6	9	12.2
7	6	8.1

Table 8: Average duration of load shedding in hours reported by mines

<i>Average load shedding duration (hours)</i>	Frequency
0.5	2
1	4
2	2
4	10
5	6
6	10
7	14
8	8
9	8
10	8
12	2

The average hours of load shedding by mines ranged from a minimum of ½ an hour per load shed for one of the mines to 12 hours for another mine (Table 8). About 14 mines experienced average length of 7 hours, 2 mines experienced maximum average duration of 12 hours per load shed and also 2 mines experienced minimum average duration of ½ an hour load shed. This reflects that mines were exposed to different load shedding of different duration. Again this has a different effect on how each mine operations is affected by load shedding. The frequency and duration of load shedding differs depending on whether there is an arrangement with the power utility by the mine for an uninterrupted power supply or not.

Table 9: Availability of uninterrupted supply and warning arrangement with power utility

	Freq	%	AWO	AOD (hrs)
Mines without arrangement	54	73.0	6	8
Mines with arrangement	20	27.0	2	2

AWO = Average weekly outages; AOD = Average outage duration (hours)

Table 9 showed that 27% surveyed mines have an arrangement with the power utility for an uninterrupted power supply, while 73% do not have. Those having an arrangement have fewer load shedding per week than those without. Also, they have lesser duration of load shedding than those without. The arrangement was signed for uninterrupted power supply contracts and advance warning between mines and the power utility where by mines pay their utility bills in foreign currency for ZESA to pay for power imports. However, all mines acknowledged that the arrangement for an uninterrupted supply and advance warning could not be achieved 100 percent with the prevailing worsened electricity supply problems.

Table 10: Decline in mining operation levels caused by load shedding

PDMO	Frequency	Percentage
Decline by 0%	1	1.4
Decline by 0-25%	7	9.5
Decline by 26-50%	23	31.1
Decline by 51-75%	26	35.1
Decline by 76-99%	13	17.6
Decline by 100% (no activity)	4	5.4

PDMO = Percentage Decline in Mining Operations

Among the surveyed mines, 5.4% shut down production at one time or another in the year due to load shedding, 35.1% between 51% and 75% decline, 31.1% between 26% and 50% decline, 17.6% between 76% and 99% decline while a single mine reported no decline.

Decomposition of Load Shedding Cost by Type of Cost: Table 11 provides a decomposition of cost by type using the mean values from the surveyed mines. The table also confirms the survey expectations that lost output is the major type of direct cost incurred by mines.

Table 11: Decomposition of direct cost by type

Cost Type	Amount (US\$)	As % of Total
Lost output	1919059.65	92.48
Labour cost	72745.95	3.51
Destruction of material (raw materials and stocks)	40816.22	1.97
Restart costs	28313.51	1.36
Damage to equipment	14156.76	0.68
Total	2075091.14	100

The mean cost totalled over two million dollars (US\$) in 2008. Using the total mean of the direct cost components, the total load shedding cost of the mining sector was found to be US\$153,556,744. The total cost for the sector translates to US\$354,840,585.

Decomposition of direct cost per mineral: Table 12 provides a decomposition of losses by type of mineral extracted. The table shows output loss cost, labour cost, material cost, other cost (restart and damage to equipment cost) and total direct cost. Some mines pointed out that output loss is more significant per load shed if the load shedding affects the whole shift in operation. Labourers have to be paid regardless of idleness due to load shedding. Low material destruction cost shows that mineral ores are not much subjected to load shedding while in stock.

Table 12: Decomposition of cost by type of mineral mined

MT	OLC(US\$)	LC(US\$)	MC(US\$)	OC(US\$)	TDC(US\$)
Gold	2688563	82725	44531	44700	2860519
Platinum	1342800	151200	53280	53280	1600560
Limestone	180000	28800	6000	15600	230400
Iron	1801680	64800	25200	34800	1926480
Vermiculite	24000	6000	42000	42000	114000
Phosphate	372000	34000	38000	22000	466000
Chrome	570000	49333	37667	34000	691000
Nickel	3000000	90000	0	18000	3108000
Diamond	700000	104000	126000	134000	1064000
Coal	3612000	75000	9000	105000	3801000
Lithium	2970000	66000	96000	12000	3144000
Graphite	180000	90000	6000	18000	294000
Black Granite	2080000	26000	8000	16000	2130000
Asbestos	4200000	54000	30000	30000	4314000

MT = Mineral Type; OLC = Output Loss Cost; LC = Labour Cost; MC = Material Cost; OC = Other Cost; TDC = Total Direct Cost

From the table 12, asbestos have the highest output loss cost while vermiculite has the lowest. However, it was different with labour cost where platinum has the highest while vermiculite the least again. For material destruction cost, diamond reported the highest

while nickel reported the lowest with zero cost. Diamond mines reported the highest for other cost while limestone the least. Overall, asbestos reported the highest total direct cost while vermiculite reported the lowest cost.

Distribution of cost per kwh lost by mineral type: Load shedding cost per KWH lost was obtained by adding all the direct cost. Annual KWHs of unsupplied electricity due to load shedding from the power utility grid were also computed. A simple division was then performed dividing total direct cost by unsupplied KWHs.

Table 13: Distribution of per kwh cost by power capacity, scale, location and mineral

Factor		PLC per kwh (US\$)
Power Supply Capacity	High Capacity (HC) mines	26
	Low Capacity (LC) mines	91
Scale of Operation	Small Scale	79.07
	Medium Scale	74.26
	Large Scale	59.43
City of Location	Harare	75
	Bulawayo	10
	Mutare	37
	Kwekwe	58
	Kadoma	21
	Chegutu	20
	Chinhoyi	27
	Other areas	63
	Mineral Type	Gold
	Platinum	19
	Limestone	22
	Iron	16
	Vermiculite	2
	Phosphate	23
	Chrome	41
	Nickel	56
	Diamond	13
	Coal	32
	Lithium	49
	Graphite	12
	Black Granite	47
	Asbestos	61

PLC = Production Loss cost

Table 13 shows load shedding cost per kwh. Among the minerals, asbestos, nickel and gold mines recorded the highest load shedding cost per kwh ranging between US\$54 to US\$61, followed by lithium, black granite, chrome and coal mines ranging between US\$32 to US\$ 49, then phosphate, limestone, platinum, iron, graphite and diamond mines ranging between US\$12 to US\$23 and vermiculite reported the lowest cost of US\$2 per kwh. The overall mean kwh cost was found to be US\$31.07. The cost variation across location is also presented on table 13. Of the locations, mines around Harare reported the highest load shedding cost per kwh of US\$75, followed by other small mining towns reporting US\$63 per kwh, while Bulawayo reported the lowest load shedding cost of

US\$10 per kwh. In terms of electricity supply distribution voltage, Low Capacity (LC) reported the higher load shedding cost per unsupplied kwh of US\$91 and High Capacity (HC) mines reported load shedding cost of US\$26 per kwh unsupplied. This reflects the presence of arrangement between the power utility and HC mines. Using the average kwh cost of US31.07, the total direct cost incurred by mines due to unsupplied kwhs is US\$154179096 for 2008 with an average cost per mine of US\$2083501. Considering the total number of mines connected to the grid, this translates to US\$356278721. The two approaches to direct assessment method shows a smaller difference of load shedding cost, hence reflecting reliability of the data obtained using questionnaires.

The relationship of the factors which contribute to the level of load shedding cost was modelled by assuming a simple linear relationship between load shedding cost and observed variables. The relevant dependent and independent variables making up the model, together with expected signs of their coefficients are described on table 14.

Table 14: Description of all variables used in multiple regressions

Dependent Variable	Description	Expected Sign
TDCOST	Total direct cost incurred by mines as a result of electricity load shedding	
Independent Variables		
TONUOUT	Total number of outages through load shedding	+
ADHORS	Average duration of load shedding in hours	+
TOKWHLOS	Total kwh lost	+
TWHRS	Total working/operational hours (business hours)	+
CAPACITY	Capacity level of operation	+
REV	Revenue income from the mine	-
ELEXP	Electricity expenditure	-
NEMPL	Number employed	+
DUMARR	Dummy for uninterrupted supply arrangement: 1 for arrangement and 0 otherwise	-
DUMBE	Dummy for backup equipment: 1 for presents and 0 otherwise	-

Table 15 showed the complete OLS regression results on the determinants of load shedding cost. In the complete OLS model, the statistically significant coefficients, in the case defined as significance of less than or equal to 10% ($p \leq 0.10$) were the coefficients of the variables ADHORS, TOKWHLOS, TWHRS and DUMARR. These variables were then used in a reduced OLS model (Table 16). Although not statistically significant TONUOUT, CAPACITY and NEMPL, coefficient signs explain the relationship to load shedding cost. Similarly, the presence of backup equipment had a reduction effect on load shedding cost. Only one variable ADHORS has shown unexpected sign although significant.

Table 15: An OLS model fit to the complete determinants of load shedding cost
Dependent Variable: TDCOST; Method: Least Squares; Included observations: 74

Variable	Coefficient	Std. Error	t-Statistic	Prob.
C	275169.6	1443720.	0.190598	0.8495
TONUOUT	3306.371	3856.601	0.857328	0.3945
ADHORS	-423275.2	112328.3	-3.768198	0.0004
TOKWHLOS	2.700418	0.843590	3.201102	0.0021
TWHR	509.2823	120.5471	4.224758	0.0001
CAPACITY	15695.51	19135.96	0.820210	0.4152
REV	-0.007238	0.006249	-1.158299	0.2511
ELEXP	-0.020050	0.138995	-0.144247	0.8858
NEMPL	160.1790	784.3026	0.204231	0.8388
DUMARR	-2468656.	710083.3	-3.476572	0.0009
ABE	-173364.1	754676.2	-0.229720	0.8191
R-squared	0.479555	Mean dependent var		2075092.
Adjusted R-squared	0.396945	S.D. dependent var		2519494.
S.E. of regression	1.956554	Akaike info criterion		31.94764
Sum squared resid	241.1486	Schwarz criterion		32.29013
Log likelihood	-1171.062	Hannan-Quinn criteria.		32.08426
F-statistic	5.805023	Durbin-Watson stat		1.259181
Prob(F-statistic)	0.000004			

A minimum adjusted R-squared of 15% or more is considered acceptable (Hanley and Splash, 1993). At 39.6% for the complete OLS model, the adjusted R-squared is above minimal acceptability.

Table 16: An OLS model fit to the reduced determinants of load shedding cost
Dependent Variable: TDCOST; Method: Least Squares; Included observations: 74

Variable	Coefficient	Std. Error	t-Statistic	Prob.
C	-26496.41	1180346.	-0.022448	0.9822
TONUOUT	5284.395	3592.949	1.470768	0.0014
ADHORS	-345856.2	94610.22	-3.655590	0.0005
TOKWHLOS	2.146680	0.701349	3.060787	0.0032
TWHR	495.6780	108.1326	4.583983	0.0000
DUMARR	-2335158.	658571.7	-3.545792	0.0007
R-squared	0.450337	Mean dependent var		2075092
Adjusted R-squared	0.409921	S.D. dependent var		2519494
S.E. of regression	1,935390	Akaike info criterion		31.86712
Sum squared resid	255.3564	Schwarz criterion		32.05394
Log likelihood	-1173.083	Hannan-Quinn criteria.		31.94164
F-statistic	11.14245	Durbin-Watson stat		1.186583
Prob(F-statistic)	0.000000			

The results of OLS model provided a higher level of significance for each variable except for the constant. The results showed positive values for TONUOUT, TOKWHLOS and TWHR reflecting increase in load shedding cost due to increase in these variables and negative values for ADHORS and DUMARR reflecting decrease in load shedding cost due to increase in duration and presence of uninterrupted supply arrangement. ADHORS reported unexpected sign again (table 16).

As with the complete model, the adjusted R-squared was used as a measure of

the fit; 40.99% of the variation in load shedding cost was explained in the OLS reduced model. The adjusted R-squared value is almost similar to that observed in the complete model, suggesting that no significant variables were left out of the reduced model. It is however, unadvisable to make deductions about which model is preferred to determinants based on a perceived negligible change in the adjusted R-squared value. Additional inferential tests, such as hypothesis testing, should be used for this purpose (Hanley and Splash, 1993). The relevant hypothesis tests in this regard are:

H_{0j} : The exclude variables in the reduced model do not improve the model

The complete and reduced OLS models were compared to determine which one better fits the data using F-test. The F-statistic was calculated as follows:

$$F = \frac{SSE_R - SSE_C / \text{No. of } \beta\text{'s tested}}{MSE_C}$$

$$= \frac{(255.3564 - 241.1486)/5}{1.93539^2}$$

$$= 0.759 < F_{0.5}(563)$$

Given that the test statistic is less than the critical value, the null hypothesis cannot be rejected in favour of the alternative. It was concluded that the reduced OLS was superior to the complete OLS model for the determining the determinants of load shedding cost as the omitted variables did not significantly improve the model.

Mining Load Shedding Cost Impact Assessment: The impact of load shedding was assessed using total sector load shedding as a proportion of GDP. The load shedding cost scale was assessed as a proportion of the GDP of US\$5.4 billion for 2009 (RBZ, 2010). The impact of load shedding for the mining sector was 4.6 percent of GDP.

CONCLUSION AND RECOMMENDATIONS

One strong conclusion of the study is that poor state of electricity supply in Zimbabwe has imposed huge cost on the mining sector. The bulk of the cost come in the form of lost output or lost production. Furthermore, it is concluded that load shedding costs vary proportionately with power supply capacity and scale of operations. Small scale mines which form the greater proportion of Low Capacity (LC) mines are more heavily affected by electricity load shedding compared to High Capacity (HC) mines which form the greater proportion of large scale mines due to availability of uninterrupted power supply and advance warning arrangement signed by the majority of HC mines. It is also conclude that mineral type has an influence on the cost of load shedding, high valued minerals (diamond and gold mines) have generally reported the highest load shedding cost in both total and per unit of unsupplied kwh and low valued minerals (vermiculite mines) the least. Research results have shown that load shedding result in significant cost to mines. Therefore, it is

recommended that the power utility to increase power generation in order to reduce load shedding to mines. Power utility to communicate to the mines before load shedding them in order for them to prepare for the load shedding. Mines to concentrate on other activities which do not require electricity during load shedding times. The power utility (ZESA) should prioritise mining sector as there is a lot of potential for economic growth and employment through mining and mining related activities.

REFERENCES

- Adenikinju, A.** (2005). Analysis of the cost of infrastructure failures in a developing economy: The case of the electricity sector in Nigeria. Nairobi, Kenya: African Economic Research Consortium. Available: www.aerc.org/publications/index.asp
- Akinlo, A. E.** (2008). Energy consumption and economic growth: evidence from 11 Sub-Sahara African countries, *Energy Economics*, 30, 2391- 2400.
- Andrews-Speed, P. and Dow, S.** (2000). Reform of China's electric power industry, *Energy Policy*, 28(5), 335-347.
- Asian Development Bank** (1997). *Handbook for the Economic Analysis of electricity Supply Projects*. Manila: Asian Development bank.
- Beenstock, M., Goldin, E. and Haitovsky, Y.** (1998). Response Bias in a Conjoint Analysis of Power Outages. *Energy Economics*, 20(2), 135-156.
- Bernstein, M. and Heganazy, Y.** (1988). Economic costs of electricity shortages: Case study of Egypt. *The Energy Journal, Special Electricity Reliability Issues*, 9, 173-88.
- Bose, R. K., Shukla, M. Srivasta, L. and Yaron, G.** (2006). Cost of unserved Power in Karnataka, India. *Energy Policy*, 34(12), 1434-1447.
- Boston Institute for Development Economics** (2006). Impact of privatisation in Africa: Synthesis of Eight Case Studies. Public Private Infrastructure Advisory Facility.
- Calderon, C.** (2008). Infrastructure and Growth in Africa. Working Paper, Africa Infrastructure Country Diagnostic.
- Chamber of Mines of Zimbabwe** (2010). Chamber of Mines Journal, Harare, Zimbabwe.
- Cochran W. G.** (1977). *Sampling Techniques* (2nd Edition). New York, USA: John Wiley and Sons.
- Confederation of Zimbabwean Industries (CZI)** (2009). Manufacturing Sector Survey for 2009. Harare, Zimbabwe.
- De Nooij, M., Kopmans, C. and Bijvoet, C.** (2006). The value of supply security and cost of power interruptions: Economic input for damage reduction and investment in networks. *Sciece Technology Journal*, 23, 231-256.
- Ebohon, O. J.** (1996). Energy, economic growth and causality in developing countries: a case study of Tanzania and Nigeria. *Energy policy*, 24 (5), 447-453.
- Eto J., Koomey J., Lehman B., Martin N., Mills E., Webber C. and Worrell E.** (2001). Scoping Study on Trends in the Economic Value of Electricity Reliability to the U.S. Economy. Barkeley, CA: Lawrence Berkeley National Laboratories, Pub LBNL-47911: pp. 1-23.
- Eto J., Divan D. and Brumsickle W.** (2004). Pilot Evaluation of Electricity-Reliability and Power-Quality Monitoring in California's Silicon Valley with the I-Grid System. Barkeley, CA: Lawrence Berkeley National Laboratory. LBNL-52740: pp. 1-34.
- European Commission** (1993). Growth, competitiveness, employment: the challenges and ways forward into the 21st century. European Union, Brussels: *White paper COM*, 93, 700.
- Foster, V. and Steinbuks, J.** (2008). Paying the price for unreliable power supplies: In-house generation of electricity by firms in Africa. Africa Infrastructure Country Diagnostic.
- Ferguson R., Wilkinson W. and Hill R.** (2000). Electricity use and economic development. *Energy Policy*, 28, 923-934.
- Hanley, N. and Splash, C.** (1993). *Cost? Benefit Analysis and the Environment*. Aldershot: Edward Elgar.

- Ikeme, J. and Ebohon, O. J.** (2005). Nigeria's electric power sector reform: what should form the key objectives? *Energy Policy*, 33, 1213-1221.
- Kayo, D.** (2001). Power sector reform in Zimbabwe: Proceedings of a regional policy seminar on power reforms in Africa. Nairobi, Kenya: AFREPREN. Available: www.afrepre.org/Pubs/wpp1.htm.
- Kayo, D.** (2002). Power sector reform in Zimbabwe: Will reforms increase electrification and strengthen local participation? *Energy Policy*, 30.
- Lee, K. S. and Anas, A.** (1992). Impacts of Infrastructure Deficiencies on Nigerian Manufacturing: Private Alternative and Policy Options. Washington DC, USA: Infrastructure and Urban Development Department.
- Lee, C. and Chang, C.** (2006). The impact of energy consumption on economic growth: Evidence from linear and nonlinear models in Taiwan. *Energy Policy*, 32 (12), 2282-2294.
- Ministry of Energy and Power Development** (2005). Annual Report, Harare, Zimbabwe
- Ministry of Mines** (2009). Annual Report, Harare, Zimbabwe.
- Ontario Hydro** (1980). Ontario Hydro survey on Power System Reliability: Viewpoint of Farm Operators. Final Report No. R&U 78-5, December.
- Pineau, P. O.** (2002). Electricity sector reform in Cameroon: is privatisation the solution? *Energy Policy*, 30, 11-12, 999-1012.
- Pollit M., Jamasb T. and Yu, W.** (2006). *Incorporating the price of Quality in Efficiency Analysis: The case of Electricity Distribution Regulation in the UK*. Cambridge, UK: University of Cambridge.
- Primen L.** (2001). The Cost of Power Disturbances to Industrial and Digital Economy Companies. Primen; TR-1006274. Available: EPRI. June 29. Madison WI.
- Rose, A. and Lim, D.** (2002). Business Interruption Losses from Natural Hazards: Conceptual and Methodology Issues in the Case of the Northridge Earthquake. *Environmental Hazards: Human and Social Dimensions*, 4, 1-14.
- Rose, A., Oladosu, G. and Salvino, D.** (2004). *Regional Economic Impacts of Electricity Outages in Los Angeles: A Computable General Equilibrium Analysis*. In M. Crew & M. Spiegel (Eds.). *Obtaining the Best from Regulation and Competition*. Dordrecht: Kluwer.
- Rosenberg, N.** (1998). The role of electricity in industrial development. *The Energy Journal*, 19(2), 7-24.
- Templet, P. H.** (1999). Energy, diversity and development in economic systems: an empirical analysis. *Ecological Economics*, 30 (2), 223-233.
- Tierney, K.** (1997). Impacts of Recent Disasters on Businesses: The 1993 Midwest Floods and the 1994 Northridge Earthquake. In Jones, B. (Ed.). *Economic Consequences of Earthquakes: Preparing for the Unexpected*. Buffalo, NY: National Center for Earthquake Engineering Research.
- Ukpong, I. I.** (1973). The economic consequences of electric power failures. *Nigerian Journal of Economic and Social Studies*, 15 (1), 53-74.
- World Bank** (2004a). *Making Services Work for Poor People*. World Development Report. Washington, DC: The World Bank.
- World Bank** (2004b). Azerbaijan. Raising Rates: Short-Term Implications of Residential Electricity Tariff Rebalancing. Europe and Central Asia Environmentally and Socially Sustainable Development Department Report, No. 30749-AZ.
- ZESA** (2001). Harare, Zimbabwe: Annual Report.
- ZESA** (2003). Harare, Zimbabwe: Annual Report.
- ZESA** (2004). Harare, Zimbabwe: Annual Report.
- ZESA** 2005. Harare, Zimbabwe: Annual Report.
- ZESA** 2006. Harare, Zimbabwe: Annual Report.
- ZESA** 2007. Harare, Zimbabwe: Annual Report.
- ZESA** 2008. Harare, Zimbabwe: Annual Report.
- ZESA** 2009. Harare, Zimbabwe: Annual Report.
- Zimbabwe Power Company (ZPC), subsidiary of ZESA. 2009. Annual Report, Harare, Zimbabwe
- Zimbabwe Electricity Supply Authority (ZESA) 2009. Daily Electricity Demand Assessment, Harare, Zimbabwe: ZESA.
- ZIMSTATS**. 2009. Annual Statistics for Zimbabwe, Harare, Zimbabwe